

Series Options

Gas injection

After vacuum packing and before the bag is sealed, there is an option to add gas. This is often used to extend the shelf life, as extra protection for fragile products and to prevent discolouring of specific products.

Sensor control

Instead of the number of seconds, the required end vacuum is set in percentage (0 to 99%) with this sensor. The vacuum pump extracts air until the exact pre-set end vacuum has been reached. Regardless of the volume the pre-set end vacuum will always be reached.

Trim off seal

Easily tear off the residual plastic bag with a trim off seal.

Top and Bottom Seal

Seal bars on both the inside of the lid and on the vacuum chamber.

1-2 Trim off Seal

Consists of one 3.5 mm convex seal wire and one 1.1 mm round wire.

Cushion Protection Control

Precision Control System with 20 programs

Other Series Features

Accessories

- Filler plates
- Service kit

Additional Features

- Flexible for various-size product
- Made of stainless steel
- Optimal hygiene and low particle counts
- Robust table top chamber machine
- Filler plates for faster cycle & adjusting seal height

Food Industry Applications

AMAC specializes in professional vacuum packaging machines. AMAC offers selected models for a wide variety of FOOD packaging purposes. Vacuum packaging is an effective way to extend the shelf life of food products and protects them from the external elements. The removed air also takes away the oxygen which works to prevent airborne micro-organisms from spoiling food products. Vacuumed packages are tightly sealed, so there is no leakage. The finished package is compact and saves valuable space in the fridge and freezer.



TABLETOP SERIES FOR FOOD INDUSTRIES

AMAC is proud of its long tradition as a competent business partner evolved over the years to offer services and products that meet the needs of today's industries.

With our extensive knowledge and expertise, AMAC is a leading solution provider globally for packaging machines. Because we are in close contact with our customers, we understand the changing needs of businesses, and adapt our services and products accordingly.

We offer a wide range of packaging machines and materials serving a vast array of industries.

AMAC TECHNOLOGIES
2321 E 4TH ST. VIEW LAKE
SANTA ANA, CA 92705 USA

714-299-5899

john@amactechnologies.com

www.AMACtechnologies.com

TABLETOP SERIES

FOR THE FOOD INDUSTRY

Vacuum packing your food products reduces bacterial growth and thereby extends the shelf life of your food products. It is important to note from these examples that freshness and quality of the product at the time of vacuum packaging prior to storage is a large factor on longevity.





T-135F


User-friendly and low-maintenance

T-135F has the small footprint and easy to be placed in a busy work place. Yet, it has the basic function of other models.

Specifications Table	
Machine Dimensions (L x W x H)	20% x 17% x 15%* (525 x 450 x 385 mm)
Chamber Dimensions (L x W x H)	14% x 13% x 5%* (370 x 350 x 150 mm)
Seal Bar Length	13%* (350 mm)
Weight	106 lbs. (48 kg)
Vacuum Pump Capacity	11.18 CFM (19 m3/h)
Machine Cycle	15-30 sec.
Standard Power Requirement	110V-1-60HZ 0.75-1.0 kw



Standard Seal Bar



Option 1

Specifications Table	
Machine Dimensions (L x W x H)	20% x 18% x 17%* (520 x 480 x 450 mm)
Chamber Dimensions (L x W x H)	14% x 16% x 7" (370 x 420 x 180 mm)
Seal Bar Length	16%* (420 mm)
Weight	136 lbs (62 Kg)
Vacuum Pump Capacity	14.71 CFM (25 m3/h)
Machine Cycle	15-35 sec.
Standard Power Requirement	110V-1-60HZ 0.75-1.0 kw

T-165F

Deep drawn vacuum chamber

T-165F is a mid-size chamber model with 7" deep chamber for bulkier products. It comes with various AMAC features to process a wide variety of high-profile items.




T-165FX


All stainless steel table top model

T-165FX has the largest chamber size in this series to handle bulky and odd-shaped items. The machine comes with a variety of AMAC engineered features as listed below.


Specifications Table	
Machine Dimensions (L x W x H)	24 x 18% x 18%* (610 x 480 x 470 mm)
Chamber Dimensions (L x W x H)	18 x 16% x 7" (460 x 420 x 180 mm)
Seal Bar Length	16%* (420 mm)
Weight	147 lbs (67 kg)
Vacuum Pump Capacity	14.71 CFM (25 m3/h)
Machine Cycle	20 - 40 sec.
Standard Power Requirement	110V-1-60HZ 0.75-1.0 kw



Standard Seal Bar



Option 1



Specifications Table	
Machine Dimensions (L x W x H)	20% x 27% x 17%* (530 x 700 x 440 mm)
Chamber Dimensions (L x W x H)	16% x 20% x 7%* (410 x 520 x 185 mm)
Seal Bar Length	(2) x 16%* (410 mm)
Weight	616 lbs. (73 kg)
Vacuum Pump Capacity	14.71 CFM (25 m3/h)
Machine Cycle	20 - 40 sec.
Standard Power Requirement	110V-1-60HZ 0.75-1.0 kw

T-200F

Extra wide all-stainless steel table top model

T-200F has an extra wide and extra deep chamber to accommodate either the long items or two pieces of bags to be placed over the seal bars located at both ends of the chamber for double production throughput.

